

MLFB-Ordering data

6SL3210-5BE31-1UV0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.72
Number of phases	3 AC	Offset factor cos φ	0.95
Line voltage	380 480 V -15 % +10 %	Efficiency η	0.98
Line frequency	47 63 Hz	Filter class (integrated)	Unfiltered
Output		Ambien	t conditions
Number of phases	3 AC		E
Rated voltage	400 V	Cooling	External fan
Rated power (HO)	11.00 kW / 15.00 hp	Installation altitude	1000 m (3281 ft)
Rated power (LO)	11.00 kW / 15.00 hp	Ambient temperature	
Rated current (HO)	25.00 A	Operation	-10 60 °C (14 140 °F)
Rated current (LO)	25.00 A	Storage	-40 70 °C (-40 158 °F)
Rated current (HO) at 480V	21.00 A	Relative humidity	
Rated current (LO) at 480V	21.00 A	Max. operation	95 %
Pulse frequency	4.00 kHz	Communication	
Output frequency	0 550 Hz	Communication	USS, Modbus RTU
		Standards	
		Compliance with standards	CE, cULus, C-Tick (RCM), KC
		CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



MLFB-Ordering data

6SL3210-5BE31-1UV0



Figure similar

Mechanical data		Connections	
The Mounting position	rrough-hole mounting / wall mounting / de-by-side mounting	Max. motor cable lengt	th
		Shielded	25 m (82 ft)
	20 / UL open type	Unshielded	50 m (164 ft)
	70 kg (8.16 lb)		
	10.0 mm (9.45 in)		
-)6.5 mm (8.13 in)		
Depth 1	2.5 mm (6.79 in)		
Inputs	/ outputs		
itandard digital inputs		_	
Number	4		
Digital outputs			
Number as relay changeover con	tact 1		
Number as transistor	1		
Analog inputs			
Number	2 (Can be used as additional digital input)		
Analog outputs			
Number	1		